

## 大型数控双机联动折弯机

CNC MULTI-MACHINE TANDEM HYDRAULIC PRESS BRAKE



### 产品介绍 / Product Introduction

1. 电液伺服系统，全闭环控制滑块运行精度。
2. 独有专利技术：大型折弯机双向挠度补偿机构。
3. 可调式插片下模，满足各种工件的加工。
4. 多种辅助机构可供用户选择，使加工更加便利、高效。

1. Electro-hydraulic servo system, closed loop controls slider running accuracy.
2. The unique patented technology: bilateral deflection compensation of the large press brake.
3. Open width adjustable inserts die to meet a variety of workpieces.
4. A variety of auxiliary institutions could meet users' requirements and make the process more convenient and efficient.

### 技术参数 Technical Parameters

型号 Model	公称压力 Nominal Pressure (KN)	工作台长度 Length of Table (mm)	立柱间距 Distance between Housings(mm)	喉口深度 Throat Depth (mm)	滑块行程 Stroke (mm)	滑块速度 Ram Speed (mm/s)	最大开启高度 Open Height (mm)	主电机功率 Main Motor (KW)	油箱容积 Volume of oil tank (L)	单机重量 Weight (kg)	单机外形尺寸 Overall Dimensions (L x W x H)(mm)
2-WE67K-320/6000	3200	6000	4800	720	250	70 7.5 75	830	22	2×1400	35500	6150×4575×5070
2-WE67K-320/7000	3200	7000	5600	720	250	70 7.5 75	830	22	2×1400	38000	7150×4575×5570
2-WE67K-400/7000	4000	7000	5600	720	320	60 7 60	830	30	2×1400	46000	7150×3560×5900
2-WE67K-400/7000	4000	7000	5600	950	320	60 7 60	950	30	2×1400	50000	7150×3980×6285
2-WE67K-600/6000	6000	6000	4800	1000	320	70 7.5 75	960	45	2×1400	62000	6080×4435×7300
2-WE67K-800/6000	8000	6000	4800	1100	350	80 8 70	1250	55	2×2100	89000	6240×7180×6200
2-WE67K-1000/6000	10000	6000	4800	1400	400	70 8 70	1350	2×45	2×2100	118000	6240×8080×6600
2-WE67K-1200/7000	12000	7000	5600	1600	450	70 7 65	1550	2×45	2×2600	155000	7100×8100×7800
2-WE67K-1200/9000	12000	9000	6500	1100	450	70 7 65	1200	2×45	2×2600	165000	9240×8080×7650
2-WE67K-1600/7000	16000	7000	5600	1600	450	70 6.5 55	1550	2×55	2×3150	190000	7200×5900×7900
2-WE67K-1600/9000	16000	9000	6500	1100	450	70 6.5 55	1200	2×55	2×3150	177000	9240×8133×8250
2-WE67K-2000/9000	20000	9000	6500	1600	450	70 6.5 60	1550	2×75	2×3900	280000	9240×9050×8800
2-WE67K-2200/8000	22000	8000	6000	1100	450	70 6.5 60	1200	2×75	2×3460	245000	8240×8500×8200
2-WE67K-3000/7000	30000	7000	5240	1600	450	60 6 60	1540	4×55	2×5340	335000	7300×10600×8100

本参数若有变更，恕不另行通知。  
Due to continual improvements, specifications are subject to change without notice.